

## PROFICIENT GROUPING ALGORITHM IN MULTIHOP ENVIRONMENT WITH TYPE-2 FUZZY LOGIC

NIDA TABASSUM

M.Tech Student, Dept. of CNIS, Vaagdevi  
College of Engineering, Warangal, T.S

Dr. THANVEER JHAN

Associate Professor, Dept. of CSE, Vaagdevi  
College of Engineering, Warangal, T.S

### Abstract

*Wireless sensor networks (WSNs) are attracting attention to increasing research Extensive spectrum of applications, including monitoring, tracking and Border monitoring, intelligent transportation system for monitoring traffic density And to monitor the road conditions, and environmental applications, for example, environment Pollution, water quality, agriculture. Lifetime enhancement has constantly been a vital issue as most of the Wi-Fi sensor networks (WSNs) operate in unattended environment wherein human get entry to and monitoring are nearly infeasible. Clustering is one of the maximum powerful strategies which can arrange the system operation in related way to wait the community scalability, minimize electricity consumption, and reap prolonged network lifetime. To conquer this problem, modern researchers have prompted the proposition of many several clustering algorithms. However, maximum of the proposed algorithms overburden the cluster head (CH) in the course of cluster formation. To conquer this problem, many researchers have provide you with the concept of fuzzy common sense (FL), which is applied in WSN for decision making. These algorithms focus at the performance of CH, which will be adoptive, flexible, and clever sufficient to distribute the burden some of the sensor nodes which could beautify the community lifetime. But regrettably, most of the algorithms use kind-1 FL (T1FL) model. In this paper, we suggest a clustering algorithm on the premise of c program language period kind-2 FL model.*

**Keywords:** Type-2 Fuzzy Logic, Wireless Sensor Network, Cluster Head, Clustering Algorithm

### I. INTRODUCTION:

.A WSN is composed of a number of sensor nodes (SN) transmitting wirelessly the records they seize. An SN is generally composed of an electricity unit, processing unit, sensing unit, and communique unit. Power intake is the main limiting issue of

an SN. In reality, SNs are in preferred required to perform autonomously and independently for a huge time period in areas in which strength infrastructure might not be available. Thus, battery-powered SNs need to be able to operate with very low strength consumption. Some SNs have batteries rechargeable through solar electricity, therefore ensuring longer self-sustaining operation. The processing unit is accountable to accumulate and process alerts captured from sensors earlier than transmitting them to the network. The sensing unit is a device that produces a measurable reaction to an exchange in a physical condition like temperature or stress. The wireless communication unit is responsible for transferring the sensor measurements to the outside world, e.g., to be saved on a server, wherein they may be distributed on the internet or accessed by way of specialized employees. The wireless verbal exchange unit also can make sure a mechanism for advert-hoc communication between SNs forming a WSN [1]. In truth, in a few scenarios, it might be extra energy green to transmit a message through multi-hop communications over short distances as opposed to a single hop long distance transmission to the base station (BS). And correctly. It is noteworthy that transmission power that dominates ordinary electricity consumption is proportional to the distance between the transmitter and receiver. In order to lay outan appropriate protocol, it is important to apprehend the parameters that are

relevant to the programs. Few of them are mentioned here.

- **Self-Organizing Capability:** Sensor Networks consist of loads or thousands of sensor nodes need to have self-organizing functionality to speak with each other while they're deployed in remote places/dangerous locations without human tracking system. **Network Lifetime:** It is always anticipated that the network must be functional so long as feasible. So, all components of the node including hardware to the protocols should don't forget energy performance. **Load balancing:** Routing protocols must stability the load amongst all the sensor nodes in order that community lifetime can be more advantageous. **Scalability:** When the network grows in size, immoderate conversation overhead have to not be added despite the fact that it's miles unavoidable at the same time as building the course to the sink [2]. **Latency:** Data acquired from the sensor community is time touchy. For example, a fireplace fighter may also require timely updates for knowing the existing hearth situations whereas soil tracking machine may additionally require the document after every few hours. **Clustering:** Grouping the sensor nodes into clusters satisfy the scalability goal and attain power efficiency with prolonged network lifetime in huge scale environments. Hence designers of routing protocols need to recall the characteristics of sensor nodes, sorts of software and architectural requirements and so forth. In the previous work Low Energy Adaptive Clustering Hierarchy (LEACH) and centralized LEACH (LEACH-C), two well-known clustering based routing protocols are discussed that offers many greater possibilities for developing new protocols Instruction is

adopted i) random exam model ii) local Information for Data Transfer iii) Access to Low Energy Media iv) Control specific data processing such as overall Or compression etc. But in practice, it is not recommended Just consider a stable model or a parameter Like the energy to choose CH. Distance parameters like distanceBS, concentration and concentration can be added to select CH. The proposed algorithm makes the top [3].

## II. LITERATURE WORK:

Wireless dispensed micro-sensor systems will allow the reliable tracking of a diffusion of environments for both civil and military applications. In this paper, we have a look at communicate protocols, which can have vast impact on the overall electricity dissipation of these networks. Based on our findings that the traditional protocols of direct transmission, minimal-transmission-power, multi-hop routing, and static clustering won't be top-quality for sensor networks, we recommend LEACH (Low-Energy Adaptive Clustering Hierarchy), a clustering-based totally protocol that utilizes randomized rotation of neighborhood cluster based station (cluster-heads) to calmly distribute the power load a few of the sensors within the network [4]. LEACH makes use of localized coordination to enable scalability and robustness for dynamic networks, and includes facts fusion into the routing protocol to reduce the amount of records that ought to be transmitted to the base station. Simulations show the LEACH can achieve as much as a component of eight reduction in electricity dissipation compared with conventional time out protocols. In addition, LEACH is capable of distribute electricity dissipation flippantly at some point of the sensors,

doubling the useful device lifetime for the networks we simulated. The clustering based routing protocol perspectives that each CH inside a cluster carries the duty of turning in the message to the base station. This phase discusses most of the famous clustered based routing algorithms. As the proposed protocol ambitions at fuzzy logic concept, few FL based clustering algorithms had been mentioned here. To make it substantial, we have divided clustering algorithms into two components; one is Probabilistic Model and other is Fuzzy Logic Model [5]. In segment II-A; a few clustering algorithms were discussed based on probabilistic model and in II-B; few clustering algorithms are mentioned based totally on fuzzy logic model. Principle of LEACH. Fuzzy Logic is able to taking actual time decisions with obscure and incomplete information. It is quite simple and flexible to take real time choices below unsure surroundings. Further, T2FL version can cope with the uncertainty environment more as it should be than T1FL version because the membership levels of T2FL are themselves fuzzy units. In well known, random uncertainties are associated with probabilistic principle and Linguistic randomness is related to fuzzy sets. The strength of fuzzy units changes with distinct varieties of fuzzy fashions consisting of type-1 to type-n, considering the fact that they are supposed to cope with varying degrees of uncertainty. In this work, T2FL version is utilized in view of enhancing the routing technique with the aid of successfully electing a cluster head [6].

### III. TYPE2- FUZZY LOGIC

The sensor community is split into range of stages. The sensor nodes from sensor

network form the cluster of various size at exclusive degrees. Each cluster has a CH. The records sensed by each node is transmitted to CH. Each CH gathers the facts from its cluster participants, compresses it and sends the compressed records to the base station. Since most of the energy is dissipated throughout the transmission, the power optimization approach has been used. In the proposed model, sensor nodes are taken into consideration to be deployed uniformly to reveal the surroundings continuously.

- i) All the sensor nodes are considered to be static consisting of the bottom station.
- ii) Homogeneous networks were considered such that all of the sensor nodes have initial same energy.
- iii) Distance among the bottom station and the sensor node is computed based totally on obtained sign power indicator (RSSI).
- iv) A stand by using CH (SB-CH) is elected inside the closing degree of the chain (closer to the BS) for handing over the message to BS in case of any strength drop out happens at remaining CH. In the proposed version, CH is elected based totally on the T2FL version viewing that T2FL can cope with higher level uncertainties gift inside the complicated real global environments.

Type-2 Fuzzy Logic (T2FL) model is useful in circumstances where it's far hard to determine an exact numeric club function and there are dimension uncertainties [7]. The concept is to apply T2FL on WSN which can assist to choose an efficient CH in order that it could distribute the burden calmly amongst the sensor nodes. T2FL is characterized by using a superior membership characteristic and an inferior club characteristic. These

two features may be represented (each one) through a Type-1 fuzzy set club function. The c language among these capabilities represents the footprint of uncertainty (FOU) which is used to characterize a T2FL set.

$$Type2FL = PrincipalMF (Type1FL)$$

T2FL Model also consists of four components

Fuzzifier: Translates inputs or crisp values to fuzzy values.

2) Fuzzification Module: The inference engine combines policies and gives a mapping from enter type-2 fuzzy sets to output kind-2 fuzzy units.

3) Type Reducer/Defuzzifier: The type-reducer generates a kind-1 fuzzy set output, which is then converted to a numeric output thru walking the defuzzifier [8].

4) Knowledge base: Contains a hard and fast of fuzzy rules, and a membership characteristic set known as the information base.

**SYSTEM ARCHITECTURE:**




Fig.1 System Architecture

Fig.1 shows the proposed model for multi-hop clustering

**IV. CONCLUSION:**

The fundamental LEACH protocol is a promising protocol and gives an opportunity to improve in various elements of the communicate protocol so that the applicability of the protocol can be widely prolonged. In this paintings, the whole sensor community is divided into range of tiers and at each stage, green Cluster Head is elected based on T2FL Model. Three fuzzy descriptors including ultimate battery power, distance to base station, and attention have been taken into consideration. Each Cluster Head sends the information to the following level (beginning from the first level to the closing stage) till it reaches at the bottom station. The novelty of the protocol utilizes the concept of Type 2 FuzzyLogic justifying that fuzzy common sense version handles real timeproblems more correctly than another probabilistic model. Again, Type 2 Fuzzy Logic Model handles the measured degree of uncertainties more as it should be than Type1 Fuzzy good judgment model. Further, multi-hop communicate protocol provides a much broader scope for large software. It is concluded from simulation effects that T2FL model provides better scalability, higher lifetime in comparison to T1FL, LEACH single hop and LEACH multi-hop protocol.

**V. REFERENCES:**

[1] Vieira, M., Coelho, C., da Silva, D. & da Mata, J. [2003]. Survey on wireless sensor network devices, *Proceedings of the IEEE Conference on Emerging Technologies and Factory Automation*, pp. 537–544.

[2] W. R. Heinzelman, A. Chandrakasan, and H. Balakrishnan, "Energyefficient communication



*protocol for wireless microsensor networks,” in Proc. 33rd Hawaii Int. Conf. Syst. Sci. (HICSS), Washington, DC, USA, Jan. 2000, pp. 1–10.*

[3] J.-S. Lee and W.-L. Cheng, “Fuzzy-logic-based clustering approach for wireless sensor networks using energy predication,” *IEEE Sensors J.*, vol. 12, no. 9, pp. 2891–2897, Sep. 2012

[4] W. B. Heinzelman, A. P. Chandrakasan, and H. Balakrishnan, “An application-specific protocol architecture for wireless microsensor networks,” *IEEE Trans. Wireless Commun.*, vol. 1, no. 4, pp. 660–670, Oct. 2002.

[5] P. Nayak and D. Anurag, “A fuzzy logic-based clustering algorithm for WSN to extend the network lifetime,” *IEEE Sensor J.*, vol. 16, no. 1, pp. 137–144, Jan. 2016.

[6] Z. Arabi, “HERF: A hybrid energy efficient routing using a fuzzy method in wireless sensor networks,” in *Proc. Int. Conf. Intell. Adv. Syst. (ICIAS)*, Jun. 2010, pp. 1–6.

[7] Y.-C. Wang, F.-J. Wu, and Y.-C. Tseng, “Mobility management algorithms and applications for mobile sensor networks,” *Wireless Commun. Mobile Comput.*, vol. 12, no. 1, pp. 7–21, 2012.

[8] N. N. Karnik and J. M. Mendel, “An introduction to type-2 fuzzy logic systems,” *Univ. Southern California, Los Angeles, CA, USA, Tech. Rep.*, 1998.